

G200EI Series

High Isolation, 2W Compact MiniDIP DC/DC Converters



Key Features:

- 2W Output Power
- Compact Mini-DIP Case
- EN60950 Approved
- Single & Dual Outputs
- 3,000 VDC Isolation
- >3.5 MHour MTBF
- 24 Standard Models
- **LOW COST**



MicroPower Direct



Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Range	5 VDC Input	4.5	5.0	5.5	VDC
	12 VDC Input	10.8	12.0	13.2	
	24 VDC Input	21.6	24.0	26.4	
Input Filter	Internal Capacitor				

Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage Accuracy			±2.5		%
Output Voltage Balance	Dual Output, Balanced Loads		±1.0		%
Line Regulation	For V _{IN} Change of 1%		±1.2		%
Load Regulation	See Model Selection Guide				
Ripple & Noise (20 MHz)			75	150	mV P - P
Temperature Coefficient				±0.03	%/°C
Output Short Circuit	Momentary (1.0 Sec.)				

General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	60 Seconds	3,000			VDC
Isolation Resistance	500 VDC	1,000			MΩ
Isolation Capacitance	100 kHz, 1V		100		pF
Switching Frequency			70		kHz

EMI Characteristics, See Note 3

Parameter	Conditions	Min.	Typ.	Max.	Units
Conducted Emissions	EN 55022				Class B
ESD	EN 61000-4-2				Criteria B; ±8 kV Contact

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-40		+85	°C
Storage Temperature Range		-55		+125	°C
Cooling	Free Air Convection				
Humidity	RH, Non-condensing			95	%

Physical

Case Size	0.787 x 0.394 x 0.323 Inches (20.0 x 10.0 x 8.2 mm)				
Case Material	Non-Conductive Black Plastic (UL94-V0)				
Weight	0.07 Oz (2.1g)				

Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	3.5			MHours
Safety Standards	UL 1950, EN 60950				

Absolute Maximum Ratings

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Surge (1 Sec)	5 VDC Input	-0.7		9.0	VDC
	12 VDC Input	-0.7		18.0	
	24 VDC Input	-0.7		30.0	
Lead Temperature	1.5 mm From Case For 10 Sec			300	°C

Caution: Exceeding Absolute Maximum Ratings may damage the module. These are not continuous operating ratings.

Model Selection Guide


Model Number	Input				Output			Load Regulation		Efficiency (% Typ)	Fuse Rating Slow-Blow (mA)
	Voltage (VDC)		Current (mA)		Voltage (VDC)	Current (mA, Max)	Current (mA, Min)	% Typ.	% Max.		
	Nominal	Range	Full-Load	No-Load							
G201EI	5	4.5 - 5.5	508	32	5.0	400.0	40.0	10.0	15	81	1,000
G202EI	5	4.5 - 5.5	474	30	9.0	222.0	23.0	8.3	15	83	1,000
G203EI	5	4.5 - 5.5	469	33	12.0	167.0	17.0	6.8	15	83	1,000
G204EI	5	4.5 - 5.5	474	36	15.0	133.0	14.0	6.3	15	83	1,000
G205EI	5	4.5 - 5.5	477	37	±5.0	±200.0	±20.0	±10.0	15	82	1,000
G207EI	5	4.5 - 5.5	455	33	±12.0	±83.0	±9.0	±6.8	15	84	1,000
G208EI	5	4.5 - 5.5	464	40	±15.0	±67.0	±7.0	±6.3	15	82	1,000
G211EI	12	10.8 - 13.2	203	16	5.0	400.0	40.0	10.0	15	80	500
G212EI	12	10.8 - 13.2	201	24	9.0	222.0	23.0	8.3	15	82	500
G213EI	12	10.8 - 13.2	195	19	12.0	167.0	17.0	6.8	15	83	500
G214EI	12	10.8 - 13.2	197	18	15.0	133.0	14.0	6.3	15	83	500
G215EI	12	10.8 - 13.2	203	18	±5.0	±200.0	±20.0	±10.0	15	80	500
G217EI	12	10.8 - 13.2	190	19	±12.0	±83.0	±9.0	±6.8	15	85	500
G218EI	12	10.8 - 13.2	199	19	±15.0	±67.0	±7.0	±6.3	15	82	500
G221EI	24	21.6 - 26.4	98	9	5.0	400.0	40.0	10.0	15	80	250
G222EI	24	21.6 - 26.4	92	7	9.0	222.0	23.0	8.3	15	82	250
G223EI	24	21.6 - 26.4	95	9	12.0	167.0	17.0	6.8	15	83	250
G224EI	24	21.6 - 26.4	95	7	15.0	133.0	14.0	6.3	15	84	250
G225EI	24	21.6 - 26.4	99	9	±5.0	±200.0	±20.0	±10.0	15	82	250
G227EI	24	21.6 - 26.4	93	8	±12.0	±83.0	±9.0	±6.8	15	85	250
G228EI	24	21.6 - 26.4	98	11	±15.0	±67.0	±7.0	±6.3	15	85	250

- Notes:**
- Output load regulation is specified for a load change of 10% to 100%.
 - Operation at no load will not damage the units, but they may not meet all specifications. Recommended minimum load is given in the Model Selection Table above.
 - These converters will operate without external components. However, to meet the specified EMI limits, a simple external circuit is required. See the typical connection note at right for more information.
 - Output power should be derated linearly from 100% at 85°C to 0% at 105°C.
 - It is recommended that a fuse be used on the input of a power supply for protection. See the Model Selection table above for the correct rating.



Pin Connections

Pin	Single	Dual	Pin	Single	Dual
1	-Vin	-Vin	9	+Vout	+Vout
7	NC	NC	11	No Pin	-Vout
8	-Vout	Common	14	+Vin	+Vin

Mechanical Dimensions



Typical Connection



These converters will operate without external components. However, to further decrease input/output ripple, the simple circuit shown above is recommended.

Vin	Input Capacitor	Vout	Output Capacitors	
			Single	Dual
5 VDC	4.7 µF	5 VDC	10.0 µF	4.7 µF
12 VDC	2.2 µF	9 VDC	4.7 µF	2.2 µF
24 VDC	1.0 µF	12 VDC	2.2 µF	1.0 µF
		15 VDC	1.0 µF	0.47 µF

The table above gives the recommended values. Capacitors should be mounted as close to the converter as possible. For applications requiring very low output noise levels, a simple LC filter should be effective.

- Notes:**
- All dimensions are typical in inches (mm)
 - Tolerance x.xx = ±0.01 (±0.25)
 - Pin 1 is marked by a "dot" or indentation on the top of the unit



MicroPower Direct
 We Power Your Success - For Less!