

DIP

SIP

.25W to 1W

2W

3W

6W

8W to 10W

12W to 15W

.25W to 1W

1W to 2W

3W to 6W

	MH02S(I)
<ul style="list-style-type: none"> .25W MiniDip Case 1kV isolation, 3kV option >1.12 Mhour MTBF 40 models 	

	MG200E
<ul style="list-style-type: none"> 2W MiniDip Case Standard pin-out Single & dual outputs EN60950 approved 	

	MA300ERW
<ul style="list-style-type: none"> 3W Compact DIP case 2:1 input Standard pin-out EN60950 approved 	

	MH600RU
<ul style="list-style-type: none"> 6W MiniDip case 4:1 input Standard pin-out EN62368 approved 	

	MA800RW
<ul style="list-style-type: none"> 8W MiniDip Case 2:1 input Standard pin-out EN60950 approved 	

	MA1200RW
<ul style="list-style-type: none"> 12W 2:1 Input Standard pin-out Remote On/Off 21 models 	

	ME02S
<ul style="list-style-type: none"> .25W Ultra-mini case 1kV isolation, 3kV option Low cost Meets EN55032 	

	MD100SER
<ul style="list-style-type: none"> 1W MiniSIP Case Tight regulation 1kV isolation Load regulation Standard pin-out 	

	MD300R
<ul style="list-style-type: none"> 3W Short circuit protection 1kV isolation, 5kV option Load regulation Low cost 	

	MH05S(I)
<ul style="list-style-type: none"> .5W MiniDip Case 1kV isolation, 3.5kV option Standard pin-out Low cost 	

	MG200EI
<ul style="list-style-type: none"> 2W MiniDip Case 3kV Isolation Wide temp operation EN60950 approved 	

	MA300RW (I)
<ul style="list-style-type: none"> 3W Compact DIP case 1.5kV isolation, 3.5kV option 2:1 input Standard pin-out 	

	MG600ERU
<ul style="list-style-type: none"> 6W 4:1 input Standard pin-out 1.5 kV isolation Single & dual output 	

	MG800RU
<ul style="list-style-type: none"> 8W MiniDip Case 4:1 input EN62368 approval Single & dual output 	

	MG1200R
<ul style="list-style-type: none"> 12W MiniDip Case 4:1 input EN62368 approval Single & dual output 	

	ME05S
<ul style="list-style-type: none"> .5W Ultra-mini case 1kV isolation, 3kV option Standard pin-out Meets EN55022 	

	MD100ERW
<ul style="list-style-type: none"> 1W Short circuit protection 2:1 input 1.5 kV isolation Low cost 	

	ME300RU
<ul style="list-style-type: none"> 3W MiniSIP Case 1.6 kV isolation Short circuit protection 4:1 input 	

	MH100ERW
<ul style="list-style-type: none"> 1W 1.5 kV isolation 2:1 Input Voltage Mini Package Short Circuit Protection 	

	MG200MRR14
<ul style="list-style-type: none"> 2W MiniDip case Reinforced insulation Single & dual EN60601 approved 	

	MH300RW
<ul style="list-style-type: none"> 3W .55 x .55 case 2:1 input Short circuit protection EN62368 approved 	

	MA600RW
<ul style="list-style-type: none"> 6W 2:1 input Standard pin-out Single & dual output Standard pin-out 	

	MA800RW
<ul style="list-style-type: none"> 8W 2:1 input EN60950 approved 2:1 input EN62368 approved 	

	MA1200RU
<ul style="list-style-type: none"> 12W 4:1 input Remote on/off EN62368 approval Single & dual output 	

	MD100XE
<ul style="list-style-type: none"> 1W Short circuit protection Single & dual output 1.5 kV isolation UL approved 	

	MD100MEHI
<ul style="list-style-type: none"> 1W Compact SIP case 4.2 kV isolation Reinforced insulation EN60601 approved 	

	MD600RW(I)
<ul style="list-style-type: none"> 6W Short circuit protection MiniSip Case 1.5kV isolation, 3kV option 4:1 input Short circuit protection EN62368 approved 	

	MG100XI
<ul style="list-style-type: none"> 1W MiniDip Case 1kV to 6kV Isolation Standard pin-out 80 models 	

	MG100EI
<ul style="list-style-type: none"> 1W MiniDip Case Short circuit protection 3kV Isolation Standard pin-out 	

	MA300MRURI4
<ul style="list-style-type: none"> 3W Single & dual 1.5 kV isolation 2:1 input EN60601 approved 	

	MA300MRWR15
<ul style="list-style-type: none"> 3W Single & dual 1.5 kV isolation 4:1 input EN60601 approved 	

	MA1000RU
<ul style="list-style-type: none"> 10W Remote on/off 4:1 input EN62368 approval Single & dual output 	

	MA1500RU
<tbl_info

Module

SMT

Railway

Photovoltaic

6W to 10W

15W

20W

25W to 30W

40W to 50W

1W

2W to 6W

6W to 20W

40W to 75W

10W to 40W

MI600ERW <ul style="list-style-type: none"> • 6W • Mini 1x1 case • 2:1 input • 1.5 kV isolation • EN60950 approved

MB1500ERW <ul style="list-style-type: none"> • 15W • Mini 1x1 case • 2:1 input • 1.5 kV isolation • Remote on/off

MI2000ERW <ul style="list-style-type: none"> • 20W • Mini 1x1 case • 2:1 input • 1.5 kV isolation • Under/over voltage

MI2500RU <ul style="list-style-type: none"> • 25W • Mini 1x1 case • 2:1 input • Efficiency to 91% • Single & dual output • Standard pin-out

MB400RW <ul style="list-style-type: none"> • 40W • Compact 1x2 case • 2:1 input • Single & dual output • Standard pin-out

ML100E <ul style="list-style-type: none"> • 1W • Mini Case • Short circuit prot. • Avail. tape/reel • EN62368 approved

ML200SE <ul style="list-style-type: none"> • 2W • Ultra-mini case • 1.5 kV isolation • Avail. tape/reel • Efficiency to 85%

MR0611S <ul style="list-style-type: none"> • 6W • Mini 1x1 case • 2.25 kV isolation • Efficiency to 86% • Chassis/ Din-rail avail.

MR4011SRU <ul style="list-style-type: none"> • 40W • Compact 1x2 case • 10:1 input • 4 kV isolation • EN50155 approved

MPV1060RI4 <ul style="list-style-type: none"> • 5W & 10W • Compact case • 10:1 input • 4 kV isolation • Chassis/ Din-rail avail.

MB1000ERUI <ul style="list-style-type: none"> • 10W • Compact 1x2 case • 4:1 input • 3 kV isolation • EN60950 approved

MI1500ERW <ul style="list-style-type: none"> • 15W • Mini 1x1 case • 2:1 input • Standard pin-out • Remote on/off

MB2000ERW <ul style="list-style-type: none"> • 20W • Compact 1x2 case • 2:1 input • Efficiency to 90% • 1.5 kV isolation

MB3000ERW <ul style="list-style-type: none"> • 30W • Compact 1x2 case • 2:1 input • Efficiency to 89% • 1.5 kV isolation

MB4000ERW-H <ul style="list-style-type: none"> • 40W • Compact 1x2 case • 2:1 input • Efficiency to 91% • 1.5 kV isolation

ML100X <ul style="list-style-type: none"> • 1W • 26 standrd models • 1.5 kV isolation • Avail. tape/reel • EN62368 approved

ML200X <ul style="list-style-type: none"> • 2W • Mini SMT case • 3 kV isolation • Avail. tape/reel • Standard pin-out

MR1011S <ul style="list-style-type: none"> • 10W • Compact 1x2 case • 1.5 kV isolation • Efficiency to 85% • EN50155 approved

MR75SRW <ul style="list-style-type: none"> • 75W • 1/4 Brick • 3 kV isolation • Efficiency to 92% • EN50155 approved

MPV1580L <ul style="list-style-type: none"> • 15W • Compact case • Short circuit • 4 kV isolation • Standard pin-out

MB1000MRWRI4 <ul style="list-style-type: none"> • 10W • 2:1 input • Reinforced insulation • Single & dual • EN60601 approved

MI1500ERU <ul style="list-style-type: none"> • 15W • Mini 1x1 case • 4:1 input • 1.5 kV isolation • EN60950 approved

MB2000ERU <ul style="list-style-type: none"> • 20W • 3 kV isolation • 4:1 input • Efficiency to 90% • EN60950 approved

MB3000ERU <ul style="list-style-type: none"> • 30W • Compact 1x2 case • 2:1 input • Efficiency to 90% • 1.5 kV isolation

MB5000RW <ul style="list-style-type: none"> • 50W • Remote on/off • 2:1 input • Efficiency to 92% • 1.5 kV isolation

ML100SRI <ul style="list-style-type: none"> • 1W • 2.6 standrd models • 4.2 kV isolation • Standard pin-out • EN62368 approved

ML600RU <ul style="list-style-type: none"> • 6W • Mini SMT case • 4:1 input • Single & dual output • Avail. Tape/reel • EN62368 approved

MR1511SRU <ul style="list-style-type: none"> • 15W • Compact 1x2 case • 2.25 kV isolation • Efficiency to 85% • EN50155 approved

MR2011S <ul style="list-style-type: none"> • 20W • Compact 1x2 case • 2.25 kV isolation • Efficiency to 85% • EN50155 approved

MPV4060S <ul style="list-style-type: none"> • 40W • Compact case • Short circuit • 4 kV isolation • 200-1200 VDC

MI1000ERU <ul style="list-style-type: none"> • 10W • 4:1 input • Remote on/off • 1.5 kV isolation • EN60950 approved

MB2000ERUI <ul style="list-style-type: none"> • 20W • 3 kV isolation • 4:1 input • Efficiency to 90% • EN60950 approved

MB2000MRW4 <ul style="list-style-type: none"> • 20W • 2:1 input • Reinforced insulation • Single & dual • EN60601 approved

MI3000RU <ul style="list-style-type: none"> • 30W • Mini 1x1 case • 2:1 input • Remote on/off • EN60950 approved

MB5000RU <ul style="list-style-type: none"> • 50W • Compact 1x2 case • 2:1 input • Efficiency to 90% • 1.5 kV isolation

ML100ERW <ul style="list-style-type: none"> • 1W • 2:1 input • 1.5 kV isolation • Avail. tape/reel • Short circuit protection

ML100RW <ul style="list-style-type: none"> • 1W • 2:1 input • 1.5 kV isolation • Avail. tape/reel • Single & dual output

ML100MRI4 <ul style="list-style-type: none"> • 1W • Compact SMT case • Reinforced insulation • Single & dual • EN60601 approved