


# MPO-255 Series

## Single Output, 25W Compact, Open Frame AC/DC Power Supplies



### Key Features:

- 25W Output Power
- Universal 90-264 AC Input
- EN 60950 Compliant
- Low Leakage Current
- Nine Single Output Models
- Meets EN55022
- >500 kHour MTBF
- Only 4.2" x 2.4" x 1.1"



RoHS Compliant



MicroPower Direct



### Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

#### Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Range	Universal	90		264	VAC
		127		370	VDC
Input Frequency		47		63	Hz
Input Current	See Model Selection Guide				
Inrush Current	Cold Start, 115 VAC		20.0		A Pk
	Cold Start, 230 VAC		36.0		
Safety Ground Leakage Current	115 VAC		0.35		mA
	240 VAC		0.5		

#### Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage	See Model Selection Guide				
Output Current	See Model Selection Guide				
Output Voltage Adjustment	See Model Selection Guide				
Output Voltage Tolerance, See Note 1	See Model Selection Guide				
Ripple & Noise (20 MHz), See Note 2	See Model Selection Guide				
Hold-Up Time	115 VAC		20		mSec
	230 VAC		100		
Set-Up Time	115/230 VAC		200		mSec
Rise Time	115 VAC		30		mSec
	230 VAC		20		
Temperature Coefficient			±0.02		%/°C
Short Circuit Protection	Continuous (Autorecovery)				
Over Voltage Protection	See Note 3	115		135	%
Overload Protection	See Note 4	105			%
Over Temperature	See Note 5			U1 ≥135 °C	

#### General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	Input to Output	3,000			VAC
	Input to Ground	1,500			
	Output to Ground	500			
Isolation resistance	500 VDC		100		MΩ
EMI/RFI	Conducted		EN 55022; EN 61000-3-2, -3		
	Electrostatic Discharge (ESD)		IEC/EN 61000-4-2, -6, -8, -11		
EMC Compliance	RF Field Susceptibility		IEC/EN 61000-4-3		
	Electrical Fast Transients/Bursts On Mains		IEC/EN 61000-4-4		
Switching Frequency	Surge		IEC/EN 61000-4-5		
	Fixed		100		kHz

#### Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-10	+25	+60	°C
Storage Temperature Range		-20		+85	°C
Cooling	Free Air Convection (See Derating Curve)				
Humidity	RH, Non-condensing			95	%

#### Physical

Size	4.2 x 2.4 x 1.1 Inches (107.0 x 67.0 x 28.0 mm)				
Weight	4.9 Oz (0.14 kg)				

#### Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	300			kHours
Safety Standards	IEN 60950, IEC 60950				
Vibration	10-500 Hz, 2G 10 min/1 Cycle. Period of 60 min each along X, Y & Z Axis				


## Model Selection Guide

Model Number	Input		Output				Output Tolerance (%)	Ripple & Noise (mV p-p)	Efficiency (% Typ)
	Current (A)		Voltage (VDC)		Current (A)				
	115 VAC	230 VAC	Rated	Adjust	Rated	Range			
MPO-25S-3.3	0.60	0.40	3.3	3.14 - 3.63	5.0	0 to 5.0	±3.0	80	66
MPO-25S-05	0.60	0.40	5.0	4.75 - 5.5	5.0	0 to 5.0	±3.0	80	74
MPO-25S-7.5	0.60	0.40	7.5	7.13 - 8.25	3.3	0 to 3.3	±3.0	80	76
MPO-25S-12	0.60	0.40	12.0	11.4 - 13.2	2.1	0 to 2.1	±2.0	100	78
MPO-25S-13.5	0.60	0.40	13.5	12.8 - 14.9	1.9	0 to 1.9	±2.0	100	78
MPO-25S-15	0.60	0.40	15.0	14.25 - 16.5	1.7	0 to 1.7	±2.0	100	78
MPO-25S-24	0.60	0.40	24.0	22.8 - 26.4	1.0	0 to 1.0	±2.0	240	79
MPO-25S-27	0.60	0.40	27.0	25.65 - 29.7	0.9	0 to 0.9	±2.0	240	79
MPO-25S-48	0.60	0.40	48.0	45.6 - 52.8	0.5	0 to 0.5	±2.0	350	79

### Notes:

- Output voltage tolerance includes the effects of set point accuracy, line regulation and load regulation.
- Ripple and noise is measured at 20 MHz bandwidth using a 12 inch twisted pair wire to connect to the power supply terminals. A 0.1  $\mu$ F and a 47  $\mu$ F capacitor are connected in parallel as close to the power supply terminals as possible.
- The overvoltage protection circuit shuts down the output. The unit must be repowered to recover.
- Overload protection is provided by a "hiccup mode" circuit. The unit recovers automatically when the fault condition is removed.
- The over temperature protection circuit shuts down the output. The unit recovers automatically when the fault condition is removed.
- Mounting holes M1 and M2 should be grounded for EMI purposes.
- It is recommended that a fuse be used on the input of a power supply for protection. See the mechanical diagram for the correct rating.

## Mechanical Dimensions




### Pin Connections: CN1 (Molex 41791-03 or equiv.)

Pin	Function	Mating Housing	Terminal
1	AC-Line	Molex 2139 or Equiv.	Molex 2478 or Equiv.
3	AC-Neutral	Molex 2139 or Equiv.	Molex 2478 or Equiv.


### Pin Connections: CN2 (Molex 41791-04 or equiv.)

Pin	Function	Mating Housing	Terminal
1, 2	+Vout	Molex 2139 or Equiv.	Molex 2478 or Equiv.
3, 4	-Vout	Molex 2139 or Equiv.	Molex 2478 or Equiv.

## Static Characteristics: 24V



## Derating Curve



### Notes:

- All dimensions are typical in inches (mm)
- Tolerance x.xx = ±0.01 (±0.25)



# MicroPower Direct

**CME**  
COMPUMESS ELEKTRONIK

CompuMess Elektronik GmbH • Lise-Meitner-Str. 1 • D-85716 Unterschleißheim  
Telefon (089) 32 15 01 - 0 • Telefax (089) 32 15 01 - 11  
info@compumess.de • www.compumess.de • www.netzteile.de